

Night Scan®

The Night Scan® is a compact, low profile, roofmounted lighting system, vertically elevated to pneumatically extend up to 15 feet. Lighting is provided by a Will-Burt 12 or 24 VDC RCP directional lighting system with rotation and tilt quartz halogen lamps to provide total coverage. The remote control unit allows you to operate all Night Scan® functions and accurately aim for complete directional positioning. In addition AutoStow®, a one button command, automatically retracts and stows the entire system to the compact transport position.

Night Scan® is available in 15' (4.6m) and 11' (3.3m) heights, and supports four or six fixture lighting packages with up to 9000 watts of lighting.

- LOW PROFILE SYSTEM (12" HIGH WHEN STOWED).
- FEATURES A WIRED HANDHELD PISTOL GRIP REMOTE CONTROL FOR THE ULTIMATE EASE IN CONTROLLING THE FUNCTIONS.
- EASY TO INSTALL ON NEW VEHICLES, OR RETROFIT ON EXISTING VEHICLES.
- THE HIGH STRENGTH PRECISION 12 OR 24 VDC ACTUATOR EASILY ELEVATES MAST TO VERTICAL POSITION.
- ONE-BUTTON AUTOSTOW® PROVIDES ERROR FREE CONVENIENCE TO RETRACT AND STOW SYSTEM.
- ENVIRONMENTALLY TESTED FOR EFFECTIVE USE IN ALL WEATHER CONDITIONS.
- STURDY BASE/MOUNTING FRAME DESIGNED TO WITHSTAND STRONG WINDS.
- LIGHTS SHUT OFF AUTOMATICALLY WHEN BEING STOWED.



MODEL	LIGHTING OPTIONS	EXT. HEIGHT	STOWED DIMENSIONS
NS11-2000	2000 W/115 VAC	11 FT (3.3m)	72" x 38.5" x 12" (1829 x 978 x 305mm)
*NS11-3000	3000 W/115 VAC		65" x 42" x 12" (1651 x 1067 x 305mm)
NS11-4000	4000 W/230 VAC		72.5" x 43" x 12" (1842 x 1092 x 305mm)
NS11-6000	6000 W/230 VAC		72.5" x 43" x 12" (1842 x 1092 x 305mm)
NS11-9000	9000 W/230 VAC		79.5" x 44" x 12" (2019 x 1118 x 305mm)
NS15-2000	2000 W/115 VAC	15 FT (4.6m)	84" x 38.5" x 12" (2134 x 978 x 305mm)
*NS15-3000	3000 W/115 VAC		76.5" x 42" x 12" (1943 x 1067x 305mm)
NS15-4000	4000 W/230 VAC		83" x 43" x 12" (2108 x 1092 x 305mm)
NS15-6000	6000 W/230 VAC		83" x 43" x 12" (2108 x 1092 x 305mm)
NS15-9000	9000 W/230 VAC		90" X 44" X 12" (2286 x 1118 x 305mm)

* HAVIS SHIELD LIGHTS

UNIT WEIGHT	144 LBS. (66kg)
ERECTION TIME	55 SECONDS
WIND CAPACITY	65 MPH (110kph)
POWER REQUIREMENTS	12 VDC/20 AMPS OR 24 VDC/10 AMPS
AIR	FROM APPROVED AIR SOURCE; PRESET INSTALLED REGULATOR ALLOWS FOR INCOMING AIR PRESSURE FROM 15 TO 120 PSI.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

STANDARD EQUIPMENT

- Pistol grip handheld remote on 25'(1.6m) cable
- RCP rotation & tilt positioner
- Four or six light fixtures
- Vertical look-up floodlight for added safety.

- Mounting frame with built-in tilt system
- One button Auto Stow®
- Owner's manual with mounting and service instructions.
- One year limited warranty

OPTIONAL EQUIPMENT

- Automatic or switchable strobe

DISTRIBUTED BY:

Direction Technology, Inc. PO Box 911, Centreville, Virginia 20122-0911
(703) 222-6275 Phone (703) 222-1096 Fax email: dtione@erols.com Website:directionfinder.com